



Product Information

PowerTech SM SAE 0W-20

Item No. 1000

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Description

A fuel economy SAE 0W20 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a high fuel economy
- a high and stable viscosity index
- a good resistance against shearing
- a very fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

A fuel economy, specially formulated engine oil suitable for petrol and diesel engines of Volvo cars where the manufacturer prescribes a product that meets the specification VCC RBS0-2AE with viscosity SAE 0W20.

Specifications

ACEA C5
API SN
Volvo VCC RBS0-2AE

Typicals

Density at 15 °C, kg/l	0,847
Viscosity -35 °C, mPa.s	5570
Viscosity 40 °C, mm ² /s	45,90
Viscosity 100 °C, mm ² /s	8,70
Viscosity Index	173
Flash Point COC, °C	220
Pour Point, °C	-48
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,80