

T.G.Autoteile GmbH

Telefon.: +49 6241 2037010 Mobil.: +49 (0)159 0179 2469 Email: info@voxlube.com Website: www.voxlube.com

Bennigsenstr. 9 D-67549 Worms

Product Information

PowerTech VS SAE 0W-20

Item No. 1001

 technology, based on specially sel balanced choice of advanced addi lower fuel consumption reduced formation of combustio a very fast cold start a safe lubrication film at high ter extended oil drain intervals 	
 a very good detergency and dis a very strong protection against dark green color. 	persion
in petrol and diesel engines, with c cars and delivery vans with extend contributes to the extension of the	osed motor oil, is recommended for use or without turbo-charging, in passenger led oil drain intervals. This motor oil also lifetime of particle filters. This oil has nes for which an oil with the specification
ACEA C5 Approved under VW 508.00/509.0 Meets the requirements of: Porsche C20	0
Density at 15 °C, kg/l Viscosity -35 °C, mPa.s Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g Sulphate Ash, %	0,847 5450 44,80 8,53 171 226 -51 8,7 0,80
	 extended oil drain intervals a very good detergency and dis a very strong protection against dark green color. This fuel economy, specially comp in petrol and diesel engines, with of cars and delivery vans with extend contributes to the extension of the been specially developed for engin VW 508.00 / 509.00 is prescribed. ACEA C5 Approved under VW 508.00/509.0 Meets the requirements of: Porsche C20 Density at 15 °C, kg/I Viscosity -35 °C, mPa.s Viscosity 100 °C, mm ² /s Viscosity Index Flash Point COC, °C Pour Point, °C Total Base Number, mgKOH/g

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-holice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website..