



Product Information

PowerTech G2 SAE 0W-16

Item No. 1003

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Description

A fuel economy SAE 0W16 motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a good resistance against shearing
- a very fast cold start, even at very low temperatures
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application

This fuel economy, specially composed SAE 0W16 motor oil, is recommended for use in petrol engines in passenger cars of Japanese OEMs, equipped with the latest techniques.

Specifications

API SP Resource Conserving
ILSAC GF-6B

Typicals

Density at 15 °C, kg/l	0,845
Viscosity -35 °C, mPa.s	5600
Viscosity 40 °C, mm ² /s	37,40
Viscosity 100 °C, mm ² /s	7,34
Viscosity Index	166
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	8,5
Sulphate Ash, %	0,85