



## Product Information

# PowerTech G2 SAE 0W-20

Item No. 1004

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

### Description

A modern, synthetic, fuel economy motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

A fuel economy, special composed synthetic motor oil recommended for use in petrol engines of passenger cars, which prescribe an oil with the specification GM dexos1 Ö Gen 2.

### Specifications

API SP Resource Conserving  
ILSAC GF-6A  
Meets the requirements of:  
GM dexos1 (TM) Gen 2  
Chrysler MS 6395  
Ford WSS-M2C947-A/B1 / WSS-M2C962-A1

### Typicals

Density at 15 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	4940
Viscosity 40 °C, mm <sup>2</sup> /s	44,00
Viscosity 100 °C, mm <sup>2</sup> /s	8,60
Viscosity Index	178
Flash Point COC, °C	222
Pour Point, °C	-36
Total Base Number, mgKOH/g	8,5
Sulphate Ash, %	0,85