



Product Information

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

PowerTech RS SAE 0W-30

Item No. 1005

Description

A universal synthetic motor oil, developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming.

Application

This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application.

Specifications

Performance level:
ACEA C3
API SN/CF
BMW Longlife-04
MB 229.31/229.51/229.52
Renault RN0700/0710

Typicals

Density at 15 °C, kg/l	0,847
Viscosity -35 °C, mPa.s	5640
Viscosity 40 °C, mm ² /s	59,90
Viscosity 100 °C, mm ² /s	12,20
Viscosity Index	203
Flash Point COC, °C	224
Pour Point, °C	-45
Total Base Number, mgKOH/g	8,0
Sulphate Ash, %	0,78