



Product Information

PowerTech VS SAE 0W-30

Item No. 1006

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Description

A fuel economy, synthetic motor oil, developed according the most recent technology, based on specially selected synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- mid SAPS content
- suitable for modern catalysts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This fuel economy, specially composed motor oil, is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. This motor oil also contributes to the extension of the lifetime of particle filters. Due to its special composition it is possible to apply this product for the VW 504.00/507.00 requirements, in practice also called VW Longlife III.

Specifications

ACEA C3
Approved under VW 504.00/507.00
Meets the requirements of:
Porsche C30
BMW Longlife-04

Typicals

Density at 15 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	5750
Viscosity 40 °C, mm ² /s	64,00
Viscosity 100 °C, mm ² /s	12,00
Viscosity Index	178
Flash Point COC, °C	202
Pour Point, °C	-51
Total Base Number, mgKOH/g	8,3
Sulphate Ash, %	0,78