



Product Information

PowerTech VS SAE 0W-40

Item No. 1009

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Description

A modern universal synthetic motor oil produced with high quality synthetic base oils and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This universal synthetic motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below.

Specifications

ACEA A3/B4
API SN
Meets the requirements of:
BMW Longlife-01
Ford WSS-M2C937-A
MB 229.3 / 229.5
Porsche A40
Renault RN0700/RN0710
VW 502.00/505.00

Typicals

Density at 15 °C, kg/l	0,845
Viscosity -35 °C, mPa.s	5900
Viscosity 40 °C, mm ² /s	76,90
Viscosity 100 °C, mm ² /s	13,40
Viscosity Index	180
Flash Point COC, °C	226
Pour Point, °C	-48
Total Base Number, mgKOH/g	10,3
Sulphate Ash, %	1,09