



Product Information

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

PowerTech RC SAE 0W-40

Item No. 1010

Description

A modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Specifications

Performance level:
ACEA A3/B4
API SN/CF
BMW Longlife-01
MB 229.3/226.5
Porsche A40
Renault RN0700/RN0710
VW 502.00/505.00

Typicals

Density at 15 °C, kg/l	0,844
Viscosity -35 °C, mPa.s	5620
Viscosity 40 °C, mm ² /s	75,90
Viscosity 100 °C, mm ² /s	13,50
Viscosity Index	183
Flash Point COC, °C	238
Pour Point, °C	-48
Total Base Number, mgKOH/g	10,3
Sulphate Ash, %	1,33