



## Product Information

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

## PowerTech Protect SAE 5W-40

Item No. 1024

### Description

LB Hypersynth is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.

### Application

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

### Specifications

Performance level:  
ACEA A3/B4  
API SN/CF  
BMW Longlife-01  
Fiat 9.55535-M2  
GM LL-B-025  
MB 229.3/226.5  
Porsche A40  
Renault RN0700/RN0710  
VW 502.00/505.00

### Typicals

Density at 15 °C, kg/l	0,858
Viscosity -30 °C, mPa.s	5740
Viscosity 40 °C, mm <sup>2</sup> /s	90,20
Viscosity 100 °C, mm <sup>2</sup> /s	15,00
Viscosity Index	173
Flash Point COC, °C	223
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,3
Sulphate Ash, %	1,33