



Product Information

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

PowerTech MS SAE 5W-40

Item No. 1025

Description

This motor oil is based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a good detergency and dispersion
- a safe lubrication film at high temperatures
- a strong protection against wear, corrosion and foaming

Application

This all-round motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Specifications

Performance level:
ACEA A3/B4
API SN/CF
MB 229.1
VW 501.01/505.00

Typicals

Density at 15 °C, kg/l	0,856
Viscosity -30 °C, mPa.s	5470
Viscosity 40 °C, mm ² /s	82,80
Viscosity 100 °C, mm ² /s	14,20
Viscosity Index	168
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,1
Sulphate Ash, %	1,29