



## Product Information

# PowerTech C3 SAE 5W-40

Item No. 1026

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

### Description

A synthetic universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which special additives are added to obtain the following properties:

- a fast cold start
- a safe lubrication film at high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

### Application

This synthetic universal "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its low SAPS content this product can be applied in vehicles with modern three way catalyts and diesel particle filters.

### Specifications

Performance level:  
ACEA C3  
API SN  
BMW Longlife-04  
MB 229.51  
VW 505.01

### Typicals

Density at 15 °C, kg/l	0,854
Viscosity -30 °C, mPa.s	6200
Viscosity 40 °C, mm <sup>2</sup> /s	81,90
Viscosity 100 °C, mm <sup>2</sup> /s	14,00
Viscosity Index	164
Flash Point COC, °C	236
Pour Point, °C	-30
Total Base Number, mgKOH/g	8,0
Sulphate Ash, %	0,79