



Product Information

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

PowerTech SUPER SAE 10W-40

Item No. 1031

Description

This universal motor oil is produced with special base oils that have a natural high viscosity index, to which additives are added to obtain the following properties:

- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a safe lubrication film at high temperature
- a good detergency and dispersion
- a strong protection against wear, corrosion and foaming

Application

A universal motor oil, recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

Specifications

Performance level:
ACEA A3/B3, A3/B4-08
API SL/CF
MB 229.1
VW 501.01/505.00

Typicals

Density at 15 °C, kg/l	0,869
Viscosity -25 °C, mPa.s	4700
Viscosity 40 °C, mm ² /s	92,00
Viscosity 100 °C, mm ² /s	13,80
Viscosity Index	153
Flash Point COC, °C	232
Pour Point, °C	-39
Total Base Number, mgKOH/g	8,3
Sulphate Ash, %	1,08