



Product Information

PowerTech SL SAE 15W-40

Item No. 1037

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Description

A universal, ester fortified, synthetic motor oil developed according the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application

This is a universal, ester fortified, synthetic motor oil. This oil is specially developed for passenger car engines. Moreover this lubricant is very suitable for use in petrol and diesel engines, with or without turbo-charging.

Specifications

Performance level:
ACEA C3
API SN/CF

Typicals

| | |
|--------------------------------------|--------|
| Density at 15 °C, kg/l | 0,856 |
| Viscosity -25 °C, mPa.s | 4120 |
| Viscosity 40 °C, mm ² /s | 148,70 |
| Viscosity 100 °C, mm ² /s | 22,80 |
| Viscosity Index | 183 |
| Flash Point COC, °C | 228 |
| Pour Point, °C | -39 |
| Total Base Number, mgKOH/g | 7,7 |
| Sulphate Ash, % | 0,80 |