



## Product Information

# PowerTech SL SAE 20W-50

Item No. 1038

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

### Description

A modern multifunctional motor oil, produced with high quality solvent refined base oils and additives to obtain the following properties:

- a strong detergency and dispersion power
- a strong resistance against oxidation
- a strong protection against wear
- a strong protection against corrosion and foaming
- a high and stable viscosity index
- a low tendency to evaporation

### Application

This modern multifunctional motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans.

### Specifications

Performance level:  
ACEA A3/B4  
API SL/CF  
MB 229.1  
VW 501.01/505.00

### Typicals

Density at 15 °C, kg/l	0,888
Viscosity -15 °C, mPa.s	9000
Viscosity 40 °C, mm <sup>2</sup> /s	164,00
Viscosity 100 °C, mm <sup>2</sup> /s	17,90
Viscosity Index	120
Flash Point COC, °C	238
Pour Point, °C	-24
Total Base Number, mgKOH/g	10,2
Sulphate Ash, %	1,29