

T.G.Autoteile GmbH

Telefon.: +49 6241 2037010 Mobil.: +49 (0)159 0179 2469

Bennigsenstr. 9 D-67549 Worms

Product Information

PowerTech CK-4 SAE 10W-30

Item No. 1046

Email: info@voxlube.com Website: www.voxlube.com		
Description	 SAPS high performance additive oils. This multigrade engine oil f use in high speed four stroke die the following properties: meets or exceeds the require standards excellent cold start properties: a very good shear stability an improved oxidation resistant 	nce efore the deposits and sludge are restricted
Application	This fuel economy Heavy Duty engine oil is suitable for use in both on-road and off-highway applications. This engine oil contributes to low exhaust emission and particle levels, which highly benefits the lifetime of emission control systems. By meeting the requirements of OEM's in Europe and North America this product has a wide choice of application possibilities. This product can be applied in Euro 5 and Euro 6 engines with SCR exhaust gas system and in Euro 3 and Euro 4 engines, when indicated by the manufacturer.	
Specifications	ACEA E7, E9 API CK-4/SN Mack EOS-4.5 Renault VI RLD-3 Volvo VDS-4.5 Meets the requirements of: Cat ECF-3 Cummins CES 20086 Detroit Diesel 93K222 Deutz DQC III-18 LA Ford WSS-M2C171-F1 MAN M 3775 MB 228.31 MTU Type 2.1	
Typicals	Density at 15 °C, kg/l Viscosity -25 °C, mPa.s Viscosity 40 °C, mm²/s	0,866 6110 81,20
09/01/2021	Although this overview is composed with all possible carefulness on the and/or inaccuracies in this information, especially when these are caused and the second s	



Product Information

PowerTech CK-4 SAE 10W-30

Item No. 1046

T.G.Autoteile GmbH

Bennigsenstr. 9 D-67549 Worms Telefon.: +49 6241 2037010 Mobil.: +49 (0)159 0179 2469 Email: info@voxlube.com Website: www.voxlube.com

Viscosity 100 °C, mm²/s	12,20
Viscosity Index	142
Flash Point COC, °C	224
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,0
Sulphate Ash, %	1,00