



## Product Information

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

## PowerTech SAE 15W-40 API Ci-4

Item No. 1047

### Description

LB Unifleet Ultra is a product of the LB (Level Back-up) product range. These products are based on the officially approved formulas, using the same high-quality additives, but the base oils have been replaced with equivalent alternatives. This creates equivalent products in terms of quality, with a performance level corresponding to the originally approved products. However, because no field tests have been conducted, the product may be claimed only to meet the mentioned performance levels.

### Application

This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This product is suitable for application in Euro 4 and Euro 5 engines.

### Specifications

Performance level:  
ACEA E7  
API CI-4/SL  
Cat ECF-1-a/ECF-2  
Cummins CES 20077/20078  
Detroit Diesel 93K215  
Deutz DQC III-18  
Global DHD-1  
JASO DH-1  
Mack EO-N/EO-M Plus  
MAN M 3275-1  
MB 228.3  
MTU Type 2  
Renault VI RLD-2  
Volvo VDS-3

### Typicals

Density at 15 °C, kg/l	0,874
Viscosity -20 °C, mPa.s	5060
Viscosity 40 °C, mm <sup>2</sup> /s	106,00
Viscosity 100 °C, mm <sup>2</sup> /s	14,60
Viscosity Index	142
Flash Point COC, °C	228
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43