



## Product Information

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

## PowerTech ATF VN2 Green

Item No. 2007

### Description

A high performance synthetic fluid for modern continuously variable transmissions, based on synthetic base oils, formulated with special additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- ideal friction performance, for both CVT belt and CVT chain
- seal compatibility for better leakage prevention
- high superior anti-shudder performance
- extended service interval in combination with a longer transmission life

### Application

This high quality synthetic fluid is designed for application in continuously variable automatic gear boxes (including hybrid applications). The so called CVTF's.

### Specifications

Performance level:

Chrysler/Dodge/Jeep NS-2 / Mopar CVTF+4  
Daihatsu Amix CVTF DC / DFC / DFE  
Ford WSS-M2C928-A / Hybrid e-CVT  
GM DEX-CVT / 1940713 / 1940714  
Honda HMMF (without starting clutch) / HCF2 / iMMD  
Hyundai/Kia CVT-1 / SP III (CVT model)  
Jatco CVT 8 Hybrid  
Mazda JWS 3320  
MB 236.20  
Mitsubishi SP-III (only CVT) / CVTF J1/(ECO)J4/J4+  
Mini Cooper EZL 799 / 799A  
Nissan NS-1/2/2V/3 / N-CVT  
Subaru ECVT / iCVT / iCVT FG / CVT-LV / NS-2  
Subaru Lineartronic High Torque (HT) CVTF  
Subaru Lineartronic chain CVTF / CVTF II/III  
Suzuki CVTF TC / 3320 / 4401 / NS-2 / Green 1/2/1V  
Toyota CVTF TC / FE / THSII  
VW G 052 180 / G 052 516

### Typicals

Density at 15 °C, kg/l	0,852
Viscosity 40 °C, mm <sup>2</sup> /s	35,40
Viscosity 100 °C, mm <sup>2</sup> /s	7,30
Viscosity Index	177
Flash Point COC, °C	214
Pour Point, °C	-42