



Product Information

PowerTech ATF AV8

Item No. 2014

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Description

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- a very strong dispersion, therefore sludge is restricted to a minimum
- a very low pour point
- very good stability against oxidation and thermal properties
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured.

Application

This fluid may be used for automatic gear boxes (including hybrid), electric vehicle (EV) powertrains, power steering units, torque converters and other equipment, for which an ATF is required, which exceeds ATF Dexron III and II. Its special composition causes a longer lifetime of this liquid compared with older Dexron types. This multi-vehicle ATF meets the hardware protection of the specified low viscosity fluids, like AW-2. This product cannot be used in DCT's and CVT's or when an oil with the Ford Type F/G specification is recommended.

Specifications

Performance level:

Aisin Warner JWS 3309(T-IV)/3324(WS)/AW-1/AW-2
Allison C3/C4, BMW 7045E/8072B/LA2634/ATF6/Mini
Cat TO-2, Chrysler Dodge Mopar AS68RC/69RC (T-IV)
Chrysler ATF+/-2/+3, Fiat Type IV/9.55550-AV5/AV-6
Daihatsu ATF D-II/D-III SP
Ford Mercon/LV/M2C138-CJ/166-H/922-A1/924-A/938-A
GM Dexron VI/III/IIID/IIIE/IIIG/IIIH, TASA
Honda Acura DW-1/ATF-Z1(except in CVT)
Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
Hyundai/Kia JWS 3314/9638, Isuzu ATF II/III/SP/WSI
Jaguar ATF 3403 M115/JLM 20238/20292
JASO M315-2013 1A/1A-LV/2A
Mazda ATF DII/M-III/M-V/FZ/A7/F-1/S-1/N-1/3317
MB 236.1/2/3/236.5/236.7/236.8/236.9/236.41
Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ PA/MA1
Nissan Matic C/D/J/K/P/S/W, Porsche 3403-M115/T-IV
Subaru ATF/5AT/HP
Suzuki ATF 3309/3314/3317/2326/2384K, PSA B71 2340
Toyota D-II/D-III/T-III/T-IV/WS, Tesla Model S/3/X
VW G 052 025 / G 052 055 / G 052 162 / G 052 990
VW G 053 001 / G 053 025 / G 055 005 / G 055 025
VW G 055 162 / G 055 540 / G 060 162



T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Product Information

PowerTech ATF AV8

Item No. 2014

Voith 55.6335.xx (G607), Volvo 97335/97340/1161540
ZF 5HP 18FL/19FL/24A/30/4HP20, ML 05L/09/11A/B/21L

Typicals

Density at 15 °C, kg/l	0,845
Viscosity 40 °C, mm ² /s	29,60
Viscosity 100 °C, mm ² /s	5,90
Viscosity Index	149
Flash Point COC, °C	212
Pour Point, °C	-48