



Product Information

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

PowerTech ATF DW7

Item No. 2015

Description

A synthetic all purpose dual clutch transmission "DCT" fluid, based on high grade synthetic base oils in combination with optimized additive components to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties and durable, reliable clutch performance
- compatible with synthetic seals

Application

This dual clutch transmission fluid is developed to fulfill the highest demands of modern high tech dual clutch transmissions and is particularly suitable for transmissions where dual clutch, synchronizer, gear set and hydraulic control system operate with the same fluid (including hybrid applications).

Suitable for use in DCT transmissions (mainly 6, 7 and 8 speed), like: VW (Audi, Seat, Skoda), BMW Drivelogic, Chrysler Powershift, Geely, Getrag, Ford/Nissan Powershift, Mitsubishi TC-SST, Peugeot/Citroën DCS, Volvo Powershift, Porsche PDK and ZF, in accordance with the specified specifications. Not to be used for Step-AT, CVT or dry DCT applications.

Specifications

Performance level:

BMW DCTF-1 / DCTF-1+ / LT-5
BorgWarner
Bugatti Veyron
Chrysler 68044345 EA & GA
Ferrari TF DCT-F3
Ford WSS-M2C936-A / WSS-M2C218-A1
Hyundai/Kia
MB 236.21 / 236.22 / 236.24 / 236.25 / 239.21
Mitsubishi Dia-Queen SSTF-1
Porsche/ZF FFL-3
PSA 9734 S2
Renault EDC
Volvo 1161838 / 1161839
VW G 052 182 / G 052 529 / G 055 529
VW G 052 536 / G 055 536

Typicals

Density at 15 °C, kg/l	0,850
Viscosity 40 °C, mm ² /s	34,00
Viscosity 100 °C, mm ² /s	7,17
Viscosity Index	183



T.G.Autoteile GmbH
Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

Product Information

PowerTech ATF DW7

Item No. 2015

Flash Point COC, °C	201
Pour Point, °C	-48