



## Product Information

# PowerTech ATF WS

Item No. 2024

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

### Description

A very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

### Application

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIIH fluid is required.

### Specifications

Performance level:  
Allison C4/TES-389  
Cat TO-2  
Ford Mercon/M2C138-CJ/166-H  
GM Dexron IID/IIE/IIIF/IIIG/IIIH  
MAN 339 Typ Z1/V1  
MB 236.1/236.5/236.6/236.7/236.9  
Voith 55.6335 (G607)  
Volvo 97341  
ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

### Typicals

Density at 15 °C, kg/l	0,854
Viscosity 40 °C, mm <sup>2</sup> /s	35,80
Viscosity 100 °C, mm <sup>2</sup> /s	7,30
Viscosity Index	175
Flash Point COC, °C	226
Pour Point, °C	-51