



Product Information

T.G.Autoteile GmbH

Bennigsenstr. 9
D-67549 Worms
Telefon.: +49 6241 2037010
Mobil.: +49 (0)159 0179 2469
Email: info@voxlube.com
Website: www.voxlube.com

PowerTech Gear Oil 75W-80

Item No. 2033

Description

A multi-vehicle manual transmission fluid "MTF", based on high-quality synthetic base oils in combination with optimized additives, resulting in the following properties:

- proven performance in European and Asian synchronisers
- superior bearing and gear protection
- excellent cleanliness
- good low temperature performance
- robust corrosion protection
- a long durability.

Application

This multi-vehicle manual transmission oil has been specially developed for European and Asian vehicles (passenger cars and delivery vans), where the specified specifications are requested. This oil is also suitable for applications where the specified specifications are prescribed in combination with slightly different viscosities, such as 70W75, 70W90, 75W, 75W85 75W90 etc.

Specifications

Performance level:

API GL-4

BMW MTF LT-2 / LT3 / LT-4

Fiat 9.55550 - MZ1 / MZ6 / MZ7

Ford WSD-M2C200-C / WSS-M2C200-D2 / ESD-M2C186-A

GM GMW16612 / 1940004 / 19259104

GM 1940182 / 1940764 / 1940768

Honda MTF / MTF-II / MTF-III

MB 235.10

Nissan MT-XZ / MT-XZ TL (JR Type)

PSA B71 2330 / 2315 / 2316

Special gear oil, MTF 94

Tranself NFJ / NFP / TRJ / TRP / TRT / TRX / TRZ

Volvo 97308 / 97309

VW G 009 317 / G 052 171 / G 052 178

VW G 052 512 / G 055 512 / G 052 527 / G 052 726

VW G 060 726 / G 070 726 / G 50

Typicals

Density at 15 °C, kg/l	0,861
Viscosity 40 °C, mm ² /s	45,20
Viscosity 100 °C, mm ² /s	9,00
Viscosity Index	185
Flash Point COC, °C	208
Pour Point, °C	-42