



## Product Information

### T.G.Autoteile GmbH

Bennigsenstr. 9  
D-67549 Worms  
Telefon.: +49 6241 2037010  
Mobil.: +49 (0)159 0179 2469  
Email: info@voxlube.com  
Website: www.voxlube.com

## PowerTech HLP 32

Item No. 2040

### Description

A high grade EP hydraulic oil based on selected, solvent refined base oils having a natural viscosity index, under addition of additives to obtain the following properties:

- an excellent protection against wear
- a very good activity against rust and corrosion
- an excellent stability against oxidation
- very good demulsification properties
- very good deaerating and foam-suppressing properties
- good compatibility with seals and gaskets made from synthetic material
- low pour point

### Application

This type of hydraulic fluid may be used for heavy duty hydraulic equipment, as well as for light duty gear boxes and bearings. This hydraulic oil may also be used for lubrication systems, general lubrication and vacuum pumps (with the exclusion of turbines). This fluid is **not** compatible in systems, containing parts or equipment with a silver lining.

### Specifications

Performance level:  
AFNOR NF E 48-603 HM  
ASTM D 6158 HM  
Cincinnati Machine P-68  
Denison HF-0/HF-1/HF-2  
DIN 51524-2 HLP  
Eaton Brochure 694 for 35VQ25A  
GM LS-2  
ISO 11158 HM

### Typicals

Density at 15 °C, kg/l	0,869
Viscosity 40 °C, mm <sup>2</sup> /s	32,00
Viscosity 100 °C, mm <sup>2</sup> /s	5,52
Viscosity Index	102
Flash Point COC, °C	205
Pour Point, °C	-30
Acid number, mgKOH/g	0,40
Sulphate Ash, %	0,06